Cormack, J., Fotouhi, M., Adams, G. and Pipe, T. (2021) Comparison of Concentrated and Distributed Compliant Elements in a 3D Printed Gripper. In: Towards Autonomous Robotic Systems (TAROS 2021), Lincoln, United Kingdom, 08-10 Sep 2021, pp. 193-197. ISBN 9783030891763 (doi:[10.1007/978-3-030-89177-0_20](https://doi.org/10.1007/978-3-030-89177-0_20)).

This is the author's final accepted version.

There may be differences between this version and the published version. You are advised to consult the publisher's version if you wish to cite from it.

<http://eprints.gla.ac.uk/245551/>

Deposited on: 05 July 2021

Comparison of Concentrated and Distributed Compliant Elements in a 3D Printed Gripper^{*}

Jordan Cormack¹[0000–0001–8582–5455], Mohammad Fotouhi²[0000–0002–5956–4703], Guy Adams³, and Tony Pipe¹[0000–0002–8404–294X]

¹ Bristol Robotics Laboratory, University of the West of England, Bristol, England
jordan.cormack@uwe.ac.uk

² University of Glasgow, School of Engineering, Glasgow, Scotland

³ HP Inc. UK Ltd., Bristol, England

Abstract. Compliant elements overcome many of the shortfalls of using 3D printing to create mechanisms, as print artefacts such as ‘stair stepping’ can cause issues with conventional joints. One of the key decisions when designing a compliant mechanism is choosing to either concentrate the compliance into a small region that resembles a conventional hinge, or distribute it over a larger area. This research details the simulated deformation and stress difference between these two types of compliant elements for a 3D printed gripper. Results show that for the same gripper deformation, the distributed compliant element experiences much less stress, at the expense of stiffness in secondary loading directions.

Keywords: 3D Printing · Compliant Mechanism · Gripper

1 Introduction

One of the benefits to 3D printing gripping devices, is the ability to produce complex geometries which would be difficult to create using more conventional manufacturing methods. The majority of 3D printing processes create parts which are built up of many individual layers, which causes an effect known as stair-stepping on surfaces which are not perfectly parallel or perpendicular to the print bed (Figure 1). This effect can cause problems with parts which need to interface with each other like revolute joints, which can require careful calibration to perform well when 3D printed [2]. Although work has been done to improve the performance of 3D printed conventional joints [4][7], issues such as excess material/support removal still remain. Compliant mechanisms overcome these issues by consolidating multiple parts into a single element featuring some form of compliance. This not only reduces the number of parts, but can also reduce or remove backlash, noise and frictional losses as well as the need for maintenance or lubrication [5][6]. Blanes *et al.*[1] showed a single piece gripping mechanism featuring two coils to allow rotation of the digits, using an external pneumatic

^{*} This work was supported by HP Inc. UK Ltd.

Fig. 1. Stair Stepping

Fig. 2. Comparison of Concentrated and Distributed Compliant Elements

cylinder for actuation. This shows that a simple one-piece 3D printed gripper can be created to transfer a linear input motion to an opposed gripping motion.

Compliant mechanisms can be classified into two sub-divisions. The first and most common type is concentrated or lumped compliance [3], which is where a mostly rigid part has small regions where elastic deformation is concentrated as a hinge. The second type is where the compliant region is spread over a much larger area, distributing the stress concentration and compliance. Figure 2 shows two elements, one with concentrated compliance, and one with distributed compliance.

2 Compliant Gripper Simulation

Figure 3 shows the deformation of two grippers. The first features rigid elements with compliant regions concentrated as hinges. The second is the same gripper but with sections which distribute the compliance. The same 5N load is applied to the tab of each gripper in the -Y direction. It can be seen that the 5N load results in approximately the same deformation of the input tab and tips for both mechanism designs. Analysing the stress in the compliant regions showed a maximum (von-Mises) stress of 120MPa for the concentrated compliance element, and 24.6MPa for the distributed element. A significant difference, considering how similar the overall deformation is. As the tensile strength of many common 3D printing materials such as PLA, PETG, and Nylon is around 50MPa, this would cause the concentrated compliant regions to plastically deform or break completely. One observed benefit to the concentrated compliance design is that as the compliant region is much smaller, the stiffness of the part to deflections in other axes is much higher. Figure 4 shows a simulated comparison between deformation of the concentrated and distributed compliance gripper mechanisms after a 5N load is applied to the side of the tab (in the x axis, i.e., not the direction intended for operation). It can be seen that the distributed compliance regions allow much more deflection in this axis than the concentrated compliance regions. The colour scales have been matched to make visual comparison easier.

3 3D Printed Grippers

Both gripper designs were 3D printed using the Fused Filament Fabrication (FFF) process (Figure 5). Experimental testing showed that the 3D printed compliant grippers act in the same manner as the simulated grippers, with a

Fig. 3. Deformation of Concentrated and Distributed Compliance Gripper

Fig. 4. Comparison of off-axis deformation

similar amount of deflection in the intended direction, but much less stiffness in other axes on the gripper with distributed compliance. As expected from the much higher simulated stress on the concentrated compliance gripper, plastic deformation occurs, resulting in the gripper not returning to the original position. Without limiting the deformation to prevent this, the lifespan of the gripper would likely be much lower than the one with distributed compliance.

4 Conclusion

Although the concentrated compliance mechanism shows less off-axis deformation, the much higher stress causes it to plastically deform, altering the performance and likely reducing its future reliability. Distributing the compliance across a larger region reduces the stress concentration and allows the gripper to deform elastically without damage, but this does also make the gripper more susceptible to deformation in other axes. Careful consideration should therefore be taken when developing one-shot 3D printed mechanisms to ensure that the type of compliance is suitable for the desired deformation.

Fig. 5. Prototype FDM 3D printed grippers

References

- [1] Carlos Blanes, Martín Mellado, and Pablo Beltran. “Novel Additive Manufacturing Pneumatic Actuators and Mechanisms for Food Handling Grippers”. In: *Actuators* 3.3 (July 2014), pp. 205–225. ISSN: 2076-0825. DOI: [10.3390/act3030205](https://doi.org/10.3390/act3030205).
- [2] Jacques Cali et al. “3D-printing of non-assembly, articulated models”. In: *ACM Transactions on Graphics* 31.6 (2012), p. 1. ISSN: 07300301. DOI: [10.1145/2366145.2366149](https://doi.org/10.1145/2366145.2366149). arXiv: [arXiv:1212.4490v1](https://arxiv.org/abs/1212.4490v1).
- [3] Shikui Chen and Michael Yu Wang. “Designing Distributed Compliant Mechanisms With Characteristic Stiffness”. In: *ASME 2007 International Design Engineering Technical Conferences & Computers and Information in Engineering Conference*. Las Vegas, Nevada: ASME, 2007. DOI: [10.1115/detc2007-34437](https://doi.org/10.1115/detc2007-34437).
- [4] Juan Sebastian Cuellar et al. “Additive manufacturing of non-assembly mechanisms”. In: *Additive Manufacturing* 21.May 2017 (May 2018), pp. 150–158. ISSN: 22148604. DOI: [10.1016/j.addma.2018.02.004](https://doi.org/10.1016/j.addma.2018.02.004).
- [5] Abdullah T. Elgammal, Mohamed Fanni, and Abdelfatah M. Mohamed. “Design and Analysis of a Novel 3D Decoupled Manipulator Based on Compliant Pantograph for Micromanipulation”. In: *Journal of Intelligent and Robotic Systems: Theory and Applications* 87.1 (2017), pp. 43–57. ISSN: 15730409. DOI: [10.1007/s10846-016-0452-y](https://doi.org/10.1007/s10846-016-0452-y).
- [6] Wouter O. Schotborgh et al. “Dimensionless design graphs for flexure elements and a comparison between three flexure elements”. In: *Precision Engineering* 29.1 (2005), pp. 41–47. ISSN: 01416359. DOI: [10.1016/j.precisioneng.2004.04.003](https://doi.org/10.1016/j.precisioneng.2004.04.003).
- [7] Xiangzhi Wei, Yaobin Tian, and Ajay Joneja. “A study on revolute joints in 3D-printed non-assembly mechanisms”. In: *Rapid Prototyping Journal* 22.6 (Oct. 2016), pp. 901–933. ISSN: 13552546. DOI: [10.1108/RPJ-10-2014-0146](https://doi.org/10.1108/RPJ-10-2014-0146).