

Reduced-Order Aeroelastic Model for Limit-Cycle Oscillations in Vortex-Dominated Unsteady Airfoil Flows



ArunVishnu SureshBabu, PhD student
Dr. Kiran Ramesh, Lecturer
and
Dr. Ashok Gopalarathnam, Professor

Department of Mechanical and Aerospace Engineering
North Carolina State University

Aerospace Sciences Department
University of Glasgow, U.K


Acknowledgments

Funding from AFOSR, grant # FA9550-17-1-0301
PM: Dr. Douglas Smith

70th Annual meeting of the APS Division of Fluid Dynamics, Denver, Colorado, November 19-21, 2017

Background: LDVM method

- A low-order method for unsteady airfoil flows with intermittent vortex shedding from rounded leading edges
- LDVM = LESP-modulated Discrete Vortex Method
- LESP = Leading-Edge Suction Parameter
- A discrete TEV is shed at every time step to satisfy Kelvin's condition.
- The circulation distribution on the airfoil is taken to be Fourier series:



$$\gamma(\theta, t) = 2U \left[A_0(t) \frac{1 + \cos \theta}{\sin \theta} + \sum_{n=1}^{\infty} A_n(t) \sin(n\theta) \right]$$




Where θ is related to the chordwise coordinate x as: $x = \frac{c}{2}(1 - \cos \theta)$

- It was observed by Ramesh et. al [1] that the vortex shedding at LE is related to a Leading Edge Suction Parameter reaching a critical value.

$$LESP(t) = A_0(t)$$

- When LESP is above a critical value ($LESP_{crit}$) at a time step, a discrete LEV is shed so as to bring it down to the critical value.

Background: LDVM sample results




Comparison of results from experiment, RANS CFD, and LDVM theory for a SD 7003 airfoil undergoing pitch up-hold-return motion at $Re = 30,000$.

Background:

Study of Aeroelastic Limit Cycle Oscillations Using LDVM

- The LDVM framework is coupled with a structural model to investigate high-frequency limit-cycle oscillations in flows dominated by leading-edge vortex shedding [2].
- The structural model has degrees of freedom in pitch and plunge, and allows for large amplitudes and cubic stiffening.



The spring forces have the form:

$$F_h(h) = k_h f_h(h) = k_h (h + \beta_h h^3),$$

$$F_\alpha(\alpha) = k_\alpha f_\alpha(\alpha) = k_\alpha (\alpha + \beta_\alpha \alpha^3),$$

The non-dimensional equations of motion are:

$$\frac{2}{c} \ddot{h} - x_\alpha \ddot{\alpha} \cos \alpha + x_\alpha \dot{\alpha}^2 \sin \alpha + \frac{2}{c} \omega_h^2 f_h = \frac{4}{\pi} \kappa \frac{U^2}{c^2} C_l,$$

$$-\frac{2}{c} x_\alpha \cos \alpha \dot{h} + r_\alpha^2 \ddot{\alpha} + (r_\alpha \omega_\alpha)^2 f_\alpha = \frac{8}{\pi} \kappa \frac{U^2}{c^2} C_m,$$


Background:

Study of Aeroelastic Limit Cycle Oscillations Using LDVM


LCO's for a flat plate at Re=1000

Initial conditions: • $U = 0.467$ • $\alpha_0 = 10^0$ • $h_0 = 0$


Flowfield at different time instants




Pitch-amplitude variation



Plunge-amplitude variation




Wake structure




Motivation for model reduction

- Thousands of time steps are required for aero-elastic case studies.
- This leads to a huge number of discrete vortices in the flow-field.
- The computational complexity increases as $O(n^2)$ where n is the number of vortices in the flowfield.
- The consequence is that the CPU time can increase tremendously if the number of discrete vortices in the flow field keeps increasing.

Full model with a large number of discrete vortices




Equivalent model with fewer discrete vortices



Methodology: DV Amalgamation

- Discrete vortex count is reduced by amalgamating suitable pair of vortices at their centroid.



- Discrete vortex pairs are identified using a slightly modified version of Spalart's criterion [3]:

$$\frac{|\Gamma_j \Gamma_k|}{|\Gamma_j + \Gamma_k|} < 2.5E - 3 \quad \text{AND} \quad \frac{|z_j - z_k|^2}{(D_0 + d_j)^{3/2} (D_0 + d_k)^{3/2}} < 5.0E - 3$$

d_j and d_k are the distances of the DVs from the leading edge of the airfoil and $D_0 = 0.1c$.

- Besides, it is also required that the errors in the Fourier coefficients A_0 and A_1 due to amalgamation are less than 10^{-6} .
- This ensures that the leading edge suction and bound circulation are not affected.
- At most one pair of LEVs and one pair of TEVs are amalgamated at every time step.
- The tolerance values are constant for all cases studied.



Results

Case 1: Effect of varying freestream velocity : α vs t^*



Full model

Reduced order model



$U = 0.30$



$U = 0.44$



$U = 0.80$





Results

Case 1: Effect of varying freestream velocity : h/c vs t^*



Full model

Reduced order model



$U = 0.30$



$U = 0.44$





$U = 0.80$



Results

Case 1: Effect of varying freestream velocity

Comparison of predictions of the two models





Results

Case 2: Effect of varying $LESP_{critical}$: α vs t^*



Full model

Reduced order model



$LESP_{crit} = 0.10$



$LESP_{crit} = 0.15$



$LESP_{crit} = 0.20$





Results

Case 2: Effect of varying $LESP_{critical} : h/c$ vs t^*



Full model

Reduced order model



$LESP_{crit} = 0.10$



$LESP_{crit} = 0.15$





$LESP_{crit} = 0.20$



Results

Case 2: Effect of varying $LESP_{critical}$

Comparison of predictions of the two models




Conclusions

- The amalgamation algorithm shows promise in general.
- The LCO behavior predicted by the reduced order model is in good agreement with that predicted by the full model.
- Run-time savings vary from case to case:
 - CPU-time reductions vary from 44% to 6% for the cases presented.
 - The tolerance values have been kept constant for all cases.
 - It will be useful to explore the possibility of allowing the amalgamation scheme to adjust the tolerances during program execution.
- Future work will include multiple amalgamations at one time step.
- The broader objective is to extend the current study to tandem airfoils.

Wake effects on LCO characteristics for airfoils in tandem



A red vertical bar on the left side of the slide contains two white stylized icons. A horizontal red line with a tapered right end spans across the top of the slide. The text "THANK YOU!" is centered in the middle of the slide.

THANK YOU!